

Please route to :

	Init.
<input type="checkbox"/> Service	<input type="checkbox"/>
<input type="checkbox"/> Sales	<input type="checkbox"/>
<input type="checkbox"/> Parts	<input type="checkbox"/>



No. **2003-5**

Date: October 4, 2002

SUBJECT: High Altitude/Sea Level Specifications

YEAR	MODEL	MODEL NUMBER	SERIAL NUMBER
2003	All	All	All

The present bulletin supplies all information **required to modify** above mentioned models for **high altitude and sea level** riding.

For 2002 models, refer to *Service Bulletin 2002-5*.

For 2001 models, refer to *Service Bulletins 2001-1 Rev. 1 and 2001-2 Rev. 1*.

For 2000 models, refer to *Service Bulletins 2000-1 Rev. 1 and 2000-2*.

For 1999 and previous model years, refer to *High Altitude and Sea Level Data booklet*, (P/N 484 300 003).

CAUTION: The following modifications and adjustments apply for both high altitude operation as well as sea level operation.

PARTS COST AND LABOR ARE NOT COVERED BY BOMBARDIER LIMITED WARRANTY.

Next page table gives a quick access to proper page.

MODEL NAME	PAGE
Grand Touring V-1000 (Sport)	4
Grand Touring 800 (SE SDI R)/SE SDI R Europe)	9
Grand Touring 700 (SE R)	13
Grand Touring 700 (Sport)	12
Grand Touring 600 (SE R)	16
Grand Touring 600 (Sport R)	19
Grand Touring 500 (Sport/Sport Europe)	32
Grand Touring 550 F (Fan R)	28
Grand Touring 380 F (Fan R)	31
Legend V-1000 (Sport)	4
Legend 800 (SE SDI R)	9
Legend 700 (SE R)	13
Legend 700 (Sport)	12
Legend 600 (SE R)	16
Legend 600 (Sport R)	19
Legend 500 (Sport)	32
Legend 550 F (Fan R)	27
Legend 380 F (Fan R)	30
Mach Z (Tech Plus)	3
MX Z 800 (Sport/Sport R)	5
MX Z 800 (Sport R (with DPM)/X)	6
MX Z 800 (Renegade/Renegade R)	7
MX Z 800 (Adrenaline/Adrenaline R)	7
MX Z 700 (Adrenaline)	10
MX Z 700 (Adrenaline R)	11

MODEL NAME	PAGE
MX Z 600 (Trail)	17
MX Z 600 (Trail R)	18
MX Z 600 HO (Sport)	20
MX Z 600 HO (Sport R)	21
MX Z 600 HO (Sport R (with DPM)/X R)	22
MX Z 600 (Adrenaline/Adrenaline R)	23
MX Z 600 (Renegade/Renegade R)	23
MX Z 500 (Adrenaline/Trail)	25
MX Z 500 (Adrenaline R/Trail R)	26
MX Z 550 F (Fan R)	27
MX Z 380 F (Fan R)	29
Skandic 600 (WT LC/SUV LC)	33
Skandic 500 F (Fan SWT R)	34
Skandic 500 F (Fan WT R)	35
Skandic 500 F (Fan Sport R)	36
Skandic 440 F (Fan LT R)	37
Skandic 280 F (Fan R)	38
Summit 800 HO (X/X R/HM X/HM X R)	8
Summit 800 HO (Adrenaline/Adrenaline R)	8
Summit 800 HO (HM/HM R/Xtreme R)	8
Summit 700 (X/Adrenaline/HM)	14
Summit 700 (X R/Adrenaline R/HM R)	15
Summit 600 HO (Adrenaline/Adrenaline R)	24
Summit 550 F (Fan R)	28
Tundra 280 F (Fan R)	38

Mach Z (Tech Plus)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Green/Blue 414 768 200	←	←	Violet/Yellow 415 015 300	←	←
	Ramp	417 005 295	←	←	417 005 293X	←	←
	Calibration screw position	2	3	4	3	4	5
	Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
	Engagement RPM ± 100	4200	←	←	←	←	←
	Maximum RPM ± 100	8300	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Violet 414 978 300	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	0.0	←	←	←	←
	Cam angle	° (degrees)	47° - 44° (anodized) 417 126 385	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 24 tooth sprocket, 74 link chain, 13 wide.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
415 015 300	Spring (Violet/Yellow)	1
417 004 309	Pin (Hollow)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty	
Calibration	Main jet	290	←	←	←	←	←	PTO CTR MAG	
	Jet needle	8ADY1-41	←	←	←	←	←	3	
	Needle position	3	←	←	←	←	←	—	
	Slide cut-away	2.0	←	←	←	←	←	3	
	Pilot jet	50	←	←	←	←	←	3	
	Air screw	4.5	←	←	←	←	←	—	
	Valve seat	1.5	←	←	←	←	←	—	
	Needle jet	O-2 (327)	←	←	←	←	←	3	
	Float level	mm	21.0	←	←	←	←	—	
	Idle	RPM ± 200	2000	←	←	←	←	—	
	Idle throttle valve position	mm	1.3	1.4	1.4	1.5	1.5	1.6	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature	- 40°C - 40°F							PTO CTR MAG
	- 30°C - 20°F							PTO CTR MAG
	- 20°C - 4°F	290	←	←	←	←	←	PTO CTR MAG
	- 10°C 14°F							PTO CTR MAG
	0°C 32°F							PTO CTR MAG
	10°C 50°F							PTO CTR MAG
	20°C 70°F							PTO CTR MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend V-1000 (Sport)/Grand Touring V-1000 (Sport)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Red/Yellow 414 817 500		←	←	←	←	←
Ramp	607		←	600	←	←	←
Calibration screw position	3		4	2	3	4	5
Pin	417 222 594 (Solid-Long)		←	417 004 309 (Hollow)	←	←	←
Engagement RPM ± 100	2500		←	←	←	←	←
Maximum RPM ± 100	6750*		←	←	←	←	←

*For maximum performance, reach maximum values. For best fuel consumption, reach lower values.

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Pink	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	6.6	←	←	←	←	←
Cam angle	° (degrees)	50° - 40°	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
417 222 444	Ramp 600	3

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 800 (Sport/Sport R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet/Yellow 415 015 300	←	←	Green/Violet 414 762 800	←	←
Ramp		417 222 546	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5
Pin		417 004 308 (Solid)	←	←	←	←	←
Engagement RPM ± 100		3800	←	←	4100	←	←
Maximum RPM ± 100		7850	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Black 417 126 687	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	47° - 44° (anodized) 417 126 385	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 24 tooth sprocket, 74 link chain, 13 wide.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 762 800	Spring (Green/Violet)	1
404 106 100	Main jet 360	2
404 104 900	Main jet 340	2
404 101 300	Main jet 320	2
404 101 200	Main jet 300	2
404 100 500	Main jet 280	2
404 162 033	Jet needle (9DGI08-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		380	360	340	320	300	280	PTO MAG
Jet needle		9DGI07-58	←	←	9DGI08-58	←	←	2
Needle position		N.A.	←	←	2	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1500	←	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		410	390	370	350	330	310	PTO MAG
- 30°C - 20°F		390	370	350	330	310	290	PTO MAG
- 20°C - 4°F		380	360	340	320	300	280	PTO MAG
- 10°C 14°F		370	350	330	310	290	270	PTO MAG
0°C 32°F		360	340	320	300	280	260	PTO MAG
10°C 50°F		350	330	310	290	270	250	PTO MAG
20°C 70°F		330	310	290	270	250	230	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 800 (X/Sport R (DPM))

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet/Yellow 415 015 300	←	←	Green/Violet 414 762 800	←	←
Ramp		417 222 546	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5
Pin		417 004 308 (Solid)	←	←	←	←	←
Engagement RPM ± 100		3800	←	←	4100	←	←
Maximum RPM ± 100		7850	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Black 417 126 687	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	47° - 44° (anodized) 417 126 385	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 24 tooth sprocket, 74 link chain, 13 wide.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 762 800	Spring (Green/Violet)	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		380	←	←	←	←	←	PTO MAG
Jet needle		9DG107-58	←	←	←	←	←	2
Needle position		N.A.	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1500	←	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		←	←	←	←	←	←	PTO MAG
- 30°C - 20°F		←	←	←	←	←	←	PTO MAG
- 2°C - 4°F		380	←	←	←	←	←	PTO MAG
- 10°C 14°F		←	←	←	←	←	←	PTO MAG
0°C 32°F		←	←	←	←	←	←	PTO MAG
10°C 50°F		←	←	←	←	←	←	PTO MAG
20°C 70°F		←	←	←	←	←	←	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 800 (Renegade/Renegade R/Adrenaline/Adrenaline R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Violet/Yellow 415 015 300	←	←	←	←	←	←	←	←	←	←
Ramp		417 222 474	←	←	←	←	←	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5					
Pin		417 004 308 (Solid)	←	←	←	←	←	←	←	←	←	←
Engagement RPM ± 100		3800	←	←	←	←	←	←	←	←	←	←
Maximum RPM ± 100		7850	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Black 417 126 687	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	47° - 44° (anodized) 417 126 385	←	←	←	←	44° (anodized) 417 126 445	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 24 tooth sprocket, 74 link chain, 13 wide.

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 754 200	Spring (Pink/Violet)	1
417 126 445	44° (anodized) cam	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		520N	←	←	←	←	←	←	←	←	←	←	PTO MAG
Jet needle		9XDY1-59	←	←	←	←	←	←	←	←	←	←	2
Needle position		N.A.	←	←	←	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.0	←	←	←	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1500	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	1.8	2.0	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG
- 30°C - 20°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG
- 20°C - 4°F		520N	←	←	←	←	←	←	←	←	←	←	PTO MAG
- 10°C 14°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG
0°C 32°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG
10°C 50°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG
20°C 70°F		←	←	←	←	←	←	←	←	←	←	←	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Summit 800 HO (X/X R/Adrenaline/Adrenaline R/HM X/ HM X R/HM/HM R/Xtreme R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		←	Violet/Yellow 415 015 300	←	←	←	←
Ramp		←	417 222 548	←	←	←	←
Calibration screw position		1	1	2	3	4	5
Pin		417 004 308 (Solid)	417 222 477 (Hollow) with 1 set screw	←	←	417 222 477 (Hollow) no set screw	←
Engagement RPM ± 100		←	3800	←	←	←	←
Maximum RPM ± 100		←	7850	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		←	Black 417 126 687	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	←	N.A.	←	←	←	←
Cam angle	° (degrees)	←	159 track 44° (anodized) 417 126 445 144 track 47°-44° (anodized) 417 126 385	←	←	←	←

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 308	Pin (Solid)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		←	430	←	←	←	←	PTO MAG
Jet needle		←	9DH112-58	←	←	←	←	2
Needle position		←	3	←	←	←	←	—
Slide cut-away		←	2.0	←	←	←	←	2
Pilot jet		←	17.5	←	←	←	←	2
Air screw		←	1.5	←	←	←	←	—
Valve seat		←	1.5	←	←	←	←	—
Needle jet		←	P-0	←	←	←	←	2
Float level	mm	←	N.A.	←	←	←	←	—
Idle	RPM ± 200	←	1500	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		←	470	←	←	←	←	PTO MAG
- 30°C - 20°F		←	450	←	←	←	←	PTO MAG
- 20°C - 4°F		←	430	←	←	←	←	PTO MAG
- 10°C 14°F								PTO MAG
0°C 32°F								PTO MAG
10°C 50°F								PTO MAG
20°C 70°F								PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 800 (SE SDI R)/Grand Touring 800 (SE SDI R)/ Grand Touring 800 (SE SDI R Europe)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring		Blue/Yellow 414 689 500	←	←	Blue/Orange 414 639 000	←	←
Ramp		417 222 546	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
Engagement RPM ± 100		3800	←	←	4000	←	←
Maximum RPM ± 100		7850	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Spring		Black 417 126 687	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	47° - 44° (anodized) 417 126 385	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 24 tooth sprocket, 74 link chain, 13 wide.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 639 000	Spring (Blue/Orange)	1
417 004 309	Pin (Hollow)	3

NOTE: Shaded column gives factory settings.

NOTE: Arrows in the charts indicate that the preceding information is repeated.

MX Z 700 (Adrenaline)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Green/Violet 414 762 800	←	←	←	←	←
Ramp		417 222 381	←	←	←	←	←
Calibration screw position		1	1	3	5	4	6
Pin		417 004 308	417 222 477 (Hollow) with 1 set screw	←	←	417 222 477 (Hollow) no set screw	←
Engagement RPM ± 100		3800	←	←	←	←	←
Maximum RPM ± 100		8000	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Beige 414 558 900	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	8.0 17.6	←	←	←	←	←
Cam angle	° (degrees)	49° - 44° 417 126 719	←	←	←	←	←

Additional information: At 1800 m (6000 ft), un-screw red RAVE screw to be flush with RAVE cap.

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 222 477	Pin (Hollow, threaded)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		←	510N	←	←	←	←	PTO MAG
Jet needle		←	9ZLY3-58	←	←	←	←	2
Needle position		←	N.A.	←	←	←	←	—
Slide cut-away		←	2.0	←	←	←	←	2
Pilot jet		←	17.5	←	←	←	←	2
Mixture screw		←	1.5	←	←	←	←	—
Valve seat		←	1.5	←	←	←	←	—
Needle jet		←	P-0	←	←	←	←	2
Float level	mm	←	N.A.	←	←	←	←	—
Idle	RPM ± 200	←	1500	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F								PTO MAG
- 30°C - 20°F								PTO MAG
- 20°C - 4°F		510N	←	←	←	←	←	PTO MAG
- 10°C 14°F								PTO MAG
0°C 32°F								PTO MAG
10°C 50°F								PTO MAG
20°C 70°F								PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 700 (Adrenaline R)

DRIVE PULLEY

Altitude		Sea Level	Altitude				
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Green/Violet 414 762 800	←	←	←	←	←
Ramp		417 222 381	←	←	←	←	←
Calibration screw position		1	1	3	5	4	6
Pin		417 004 308	417 222 477 (Hollow) with 1 set screw	←	←	417 222 477 (Hollow) no set screw	←
Engagement RPM ± 100		3800	←	←	←	←	←
Maximum RPM ± 100		8000	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	Altitude				
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Black 417 126 687	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	50°-47° 417 126 580	←	←	←	←	←

Additional information: At 1800 m (6000 ft), un-screw red RAVE screw to be flush with RAVE cap.

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 222 477	Pin (Hollow, threaded)	3

CARBURATION

Altitude		Sea Level	Altitude					Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Calibration								
Main jet		←	510N	←	←	←	←	PTO MAG
Jet needle		←	9ZLY3-58	←	←	←	←	2
Needle position		←	N.A.	←	←	←	←	—
Slide cut-away		←	2.0	←	←	←	←	2
Pilot jet		←	17.5	←	←	←	←	2
Mixture screw		←	1.5	←	←	←	←	—
Valve seat		←	1.5	←	←	←	←	—
Needle jet		←	P-0	←	←	←	←	2
Float level	mm	←	N.A.	←	←	←	←	—
Idle	RPM ± 200	←	1500	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	Altitude					Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Temperature								
- 40°C - 40°F								PTO MAG
- 30°C - 20°F								PTO MAG
- 20°C - 4°F		510N	←	←	←	←	←	PTO MAG
- 10°C 14°F								PTO MAG
0°C 32°F								PTO MAG
10°C 50°F								PTO MAG
20°C 70°F								PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 700 (Sport)/Grand Touring 700 (Sport)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Blue/Yellow 414 689 500	←	←	←	←	←	←	←	←	←	←
Ramp		417 222 372	←	←	←	←	←	←	←	←	←	←
Calibration screw position		3	4	5	3	4	6					
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←	←	←	←	←	←
Engagement RPM ± 100		3600	←	←	←	←	←	←	←	←	←	←
Maximum RPM ± 100		8000	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Violet 414 978 300	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	47° 417 126 577	←	←	←	←	←	←	←	←	←	←

Additional information: At 1800 m (6000 ft), unscrew red RAVE screw to be flush with RAVE cap.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
404 104 900	Main jet 340	2
404 106 300	Main jet 380	2
404 101 000	Main jet 410	2
404 106 500	Main jet 450	2
404 106 800	Main jet 480	2
404 161 976	Jet needle (9ZLY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		510N	480	450	410	380	340	PTO MAG					
Jet needle		9ZLY3-58	←	←	9ZLY4-58	←	←	←	←	←	←	←	2
Needle position		N.A.	←	←	←	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		P-0	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	—	—	—	—	—	—	—	—	—	—	—	—
Idle	RPM ± 200	1500	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—	—	—	—	—	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		520N	510N	480	440	400	370	PTO MAG					
- 30°C - 20°F		510N	500	460	430	390	350	PTO MAG					
- 20°C - 4°F		510N	480	450	410	380	340	PTO MAG					
- 10°C 14°F		500	470	430	400	360	330	PTO MAG					
0°C 32°F		480	450	420	380	350	310	PTO MAG					
10°C 50°F		470	440	400	370	340	300	PTO MAG					
20°C 70°F		460	430	390	360	330	290	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 700 (SE R)/Grand Touring 700 (SE R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Blue/Yellow 414 689 500	←	←	←	←	←
Ramp		417 222 372	←	←	←	←	←
Calibration screw position		3	4	5	3	4	6
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
Engagement RPM ± 100		3600	←	←	←	←	←
Maximum RPM ± 100		8000	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet 414 978 300	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	47° 417 126 577	←	←	←	←	←

Additional information: At 1800 m (6000 ft), unscrew red RAVE screw to be flush with RAVE cap.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		510N	←	←	←	←	←	PTO MAG
Jet needle		9ZLY3-58	←	←	←	←	←	2
Needle position		N.A.	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		P-0	←	←	←	←	←	2
Float level	mm	—	—	—	—	—	—	—
Idle	RPM ± 200	1500	←	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F								PTO MAG
- 30°C - 20°F								PTO MAG
- 20°C - 4°F		510N	←	←	←	←	←	PTO MAG
- 10°C 14°F								PTO MAG
0°C 32°F								PTO MAG
10°C 50°F								PTO MAG
20°C 70°F								PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Summit 700 (X/Adrenaline/HM)

DRIVE PULLEY

Altitude		Sea Level	Altitude			
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft
Clutching						
Spring	←	Violet/Yellow 415 015 300	←	←	←	←
Ramp	←	417 222 372	←	←	←	←
Calibration screw position	3	1	3	5	4	6
Pin	417 004 308 (Solid)	417 222 477 (Hollow) with 1 set screw	←	←	417 222 477 (Hollow) no set screw	←
Engagement RPM ± 100	←	4100	←	←	←	←
Maximum RPM ± 100	←	8000	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	Altitude			
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft
Clutching						
Spring	←	Beige 414 558 900	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	←	8.0 17.6	←	←	←
Cam angle	° (degrees)	←	47° 417 126 580	←	←	←

Additional information: At 1800 m (6000 ft), un-screw red RAVE screw to be flush with RAVE cap.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 308	Pin (Solid)	3

CARBURATION

Altitude		Sea Level	Altitude				Qty	
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft		3000 m 10000 ft
Calibration								
Main jet	←	500	←	←	←	←	PTO MAG	
Jet needle	←	9ZLY3-58	←	←	←	←	2	
Needle position	←	N.A.	←	←	←	←	—	
Slide cut-away	←	2.0	←	←	←	←	2	
Pilot jet	←	17.5	←	←	←	←	2	
Mixture screw	←	1.5	←	←	←	←	—	
Valve seat	←	1.5	←	←	←	←	—	
Needle jet	←	P-0	←	←	←	←	2	
Float level	mm	—	—	—	—	—	—	
Idle	RPM ± 200	←	1500	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	Altitude				Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	
Temperature							
- 40°C - 40°F							PTO MAG
- 30°C - 20°F							PTO MAG
- 20°C - 4°F	←	500	←	←	←	←	PTO MAG
- 10°C 14°F							PTO MAG
0°C 32°F							PTO MAG
10°C 50°F							PTO MAG
20°C 70°F							PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Summit 700 (X R/Adrenaline R/HM R)

DRIVE PULLEY

Altitude		Sea Level	Altitude			
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft
Clutching						
Spring	←	Violet/Yellow 415 015 300	←	←	←	←
Ramp	←	417 222 381	←	←	←	←
Calibration screw position	3	1	3	5	4	6
Pin	417 004 308 (Solid)	417 222 477 (Hollow) with 1 set screw	←	←	417 222 477 (Hollow) no set screw	←
Engagement RPM ± 100	←	4100	←	←	←	←
Maximum RPM ± 100	←	8000	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	Altitude			
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft
Clutching						
Spring	←	Violet 414 978 300	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	←	N.A.	←	←	←
Cam angle	° (degrees)	←	44° 417 126 445	←	←	←

Additional information: At 1800 m (6000 ft), un-screw red RAVE screw to be flush with RAVE cap.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 308	Pin (Solid)	3

CARBURATION

Altitude		Sea Level	Altitude				Qty	
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft		3000 m 10000 ft
Calibration								
Main jet	←	500	←	←	←	←	PTO MAG	
Jet needle	←	9ZLY3-58	←	←	←	←	2	
Needle position	←	N.A.	←	←	←	←	—	
Slide cut-away	←	2.0	←	←	←	←	2	
Pilot jet	←	17.5	←	←	←	←	2	
Mixture screw	←	1.5	←	←	←	←	—	
Valve seat	←	1.5	←	←	←	←	—	
Needle jet	←	P-0	←	←	←	←	2	
Float level	mm	—	—	—	—	—	—	
Idle	RPM ± 200	←	1500	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	←	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	Altitude				Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	
Temperature							
- 40°C - 40°F							PTO MAG
- 30°C - 20°F							PTO MAG
- 20°C - 4°F	←	500	←	←	←	←	PTO MAG
- 10°C 14°F							PTO MAG
0°C 32°F							PTO MAG
10°C 50°F							PTO MAG
20°C 70°F							PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 600 (SE R)/Grand Touring 600 (SE R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Violet/Violet 414 817 900	←	←	Violet/Blue 415 034 900	←	←
	Ramp	417 222 372	←	←	←	←	←
	Calibration screw position	3	4	5	3	4	5
	Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
	Engagement RPM ± 100	3600	←	←	3800	←	←
	Maximum RPM ± 100	8000	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Violet 414 978 300	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←
	Cam angle	° (degrees)	47° (anodized) 417 126 577	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) chain to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
415 034 900	Spring (Violet/Blue)	1
417 004 309	Pin (Hollow)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty	
Calibration	Main jet	500	←	←	←	←	←	PTO MAG	
	Jet needle	9HGY1-58	←	←	←	←	←	2	
	Needle position	N.A.	←	←	←	←	←	—	
	Slide cut-away	2.0	←	←	←	←	←	2	
	Pilot jet	20	←	←	←	←	←	2	
	Mixture screw	1.5	←	←	←	←	←	—	
	Valve seat	1.5	←	←	←	←	←	—	
	Needle jet	N.A.	←	←	←	←	←	2	
	Float level	mm	N.A.	—	—	—	—	—	
	Idle	RPM ± 200	1600	←	←	←	←	←	—
	Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature	- 40°C - 40°F							PTO MAG
	- 30°C - 20°F							PTO MAG
	- 20°C - 4°F	500	←	←	←	←	←	PTO MAG
	- 10°C 14°F							PTO MAG
	0°C 32°F							PTO MAG
	10°C 50°F							PTO MAG
	20°C 70°F							PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 600 (Trail)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Green/White 417 222 371	←	←	Green/Blue 414 768 200	←	←					
Ramp		417 222 372	←	←	←	←	←	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5					
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←					
Engagement RPM ± 100		4100	←	←	4300	←	←					
Maximum RPM ± 100		8000	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Beige 414 558 900	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	8.0 17.6	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	47° 417 126 577	←	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
414 768 200	Spring (Green/Blue)	1
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 101 000	Main jet 410	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		500	470	440	410	390	360	PTO MAG					
Jet needle		9HGY1-58	←	←	9HGY4-58	←	←	←	←	←	←	←	2
Needle position		N.A.	←	←	2	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		20	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	2.0	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		P-0	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		520N	500	470	450	420	390	PTO MAG					
- 30°C - 20°F		510N	480	450	430	400	370	PTO MAG					
- 20°C - 4°F		500	470	440	420	390	360	PTO MAG					
- 10°C 14°F		490	460	430	410	380	350	PTO MAG					
0°C 32°F		480	450	420	400	370	340	PTO MAG					
10°C 50°F		470	440	410	390	360	330	PTO MAG					
20°C 70°F		460	430	400	380	350	320	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 600 (Trail R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Green/Violet 414 762 800	←	←	Green/Blue 414 768 200	←	←					
Ramp		417 222 372	←	←	←	←	←	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5					
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←	←	←	←	←	←
Engagement RPM ± 100		4100	←	←	4300	←	←	←	←	←	←	←
Maximum RPM ± 100		8000	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Violet 414 978 300	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	47° (anodized) 417 126 577	←	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 768 200	Spring (Green/Blue)	1
417 004 309	Pin (Hollow)	3
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 101 000	Main jet 410	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		500	470	440	410	390	360	PTO MAG					
Jet needle		9HGY1-58	←	←	9HGY4-58	←	←	←	←	←	←	←	2
Needle position		N.A.	←	←	2	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		20	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	2.0	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		P-0	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		520N	500	470	450	420	390	PTO MAG					
- 30°C - 20°F		510N	480	450	430	400	370	PTO MAG					
- 20°C - 4°F		500	470	440	420	390	360	PTO MAG					
- 10°C 14°F		490	460	430	410	380	350	PTO MAG					
0°C 32°F		480	450	420	400	370	340	PTO MAG					
10°C 50°F		470	440	410	390	360	330	PTO MAG					
20°C 70°F		460	430	400	380	350	320	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 600 (Sport R)/Grand Touring 600 (Sport R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			←	←	←	←	←	←	←	←	←	←
Clutching												
Spring		Green/Violet 414 762 800	←	←	Green/Blue 414 768 200	←	←					
Ramp		417 222 372	←	←	←	←	←	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5					
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←					
Engagement RPM ± 100		4100	←	←	4300	←	←					
Maximum RPM ± 100		8000	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			←	←	←	←	←	←	←	←	←	←
Clutching												
Spring		Violet 414 978 300	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	47° (anodized) 417 126 577	←	←	←	←	←	←	←	←	←	←

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
414 768 200	Spring (Green/Blue)	1
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 101 000	Main jet 410	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			←	←	←	←	←	←	←	←	←		
Calibration													
Main jet		500	470	440	410	390	360	PTO MAG					
Jet needle		9HGY1-58	←	←	9HGY4-58	←	←	←	←	←	←	←	2
Needle position		N.A.	←	←	2	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		20	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	2.0	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			←	←	←	←	←	←	←	←			
Temperature													
- 40°C - 40°F		530N	500	460	420	390	350	PTO MAG					
- 30°C - 20°F		520N	490	450	410	370	340	PTO MAG					
- 20°C - 4°F		500	470	430	400	360	330	PTO MAG					
- 10°C 14°F		480	450	410	380	350	310	PTO MAG					
0°C 32°F		460	430	400	360	330	300	PTO MAG					
10°C 50°F		450	420	390	350	320	290	PTO MAG					
20°C 70°F		430	400	360	330	310	280	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated

NOTE: Shaded column gives factory settings.

MX Z 600 HO (Sport)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Violet/Violet 414 817 900	←	←	←	←	←
	Ramp	417 222 596	←	←	←	←	←
	Calibration screw position	3	4	5	3	4	5
	Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
	Engagement RPM ± 100	3800	←	←	4000	←	←
	Maximum RPM ± 100	8000	←	←	←	←	←

DRIVEN PULLEY (Sport)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching	Spring	White 504 152 070	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	8.9 19.5	←	←	←	←
	Cam angle (degrees)	48°-44° 417 126 719	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
404 162 016	Jet needle (9DHI12-58)	2
404 106 100	Main jet 360	2
404 104 900	Main jet 340	2
404 101 300	Main jet 320	2
404 101 200	Main jet 300	2
404 100 500	Main jet 280	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration	Main jet	380	360	340	320	300	280	PTO MAG
	Jet needle	9DHI13-58	←	←	9DHI12-58	←	←	2
	Needle position	N.A.	←	←	2	←	←	—
	Slide cut-away	2.0	←	←	←	←	←	2
	Pilot jet	17.5	←	←	←	←	←	2
	Mixture screw	1.5	←	←	2.0	←	←	—
	Valve seat	1.5	←	←	←	←	←	—
	Needle jet	N.A.	←	←	←	←	←	2
	Float level	mm	N.A.	←	←	←	←	—
	Idle	RPM ± 200	1600	←	←	←	←	—
	Idle throttle valve position	mm	1.6	1.7	1.8	1.9	2.2	←

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature	- 40°C - 40°F	410	390	370	350	330	310	PTO MAG
	- 30°C - 20°F	390	370	350	330	310	290	PTO MAG
	- 20°C - 4°F	380	360	340	320	300	280	PTO MAG
	- 10°C 14°F	370	350	330	310	290	270	PTO MAG
	0°C 32°F	360	340	320	300	280	260	PTO MAG
	10°C 50°F	350	330	310	290	270	250	PTO MAG
	20°C 70°F	330	310	290	270	250	230	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 600 HO (Sport R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet/Violet 414 817 900	←	←	←	←	←
Ramp		417 222 596	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
Engagement RPM ± 100		3800	←	←	4000	←	←
Maximum RPM ± 100		8000	←	←	←	←	←

DRIVEN PULLEY (Sport R)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Black 417 126 687	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	(degrees)	47°-44° 417 126 385	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
404 162 016	Jet needle (9DHI12-58)	2
404 106 100	Main jet 360	2
404 104 900	Main jet 340	2
404 101 300	Main jet 320	2
404 101 200	Main jet 300	2
404 100 500	Main jet 280	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		380	360	340	320	300	280	PTO MAG
Jet needle		9DHI13-58	←	←	9DHI12-58	←	←	2
Needle position		N.A.	←	←	2	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		17.5	←	←	←	←	←	2
Mixture screw		1.5	←	←	2.0	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	—
Idle throttle valve position	mm	1.6	1.7	1.8	1.9	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		410	390	370	350	330	310	PTO MAG
- 30°C - 20°F		390	370	350	330	310	290	PTO MAG
- 20°C - 4°F		380	360	340	320	300	280	PTO MAG
- 10°C 14°F		370	350	330	310	290	270	PTO MAG
0°C 32°F		360	340	320	300	280	260	PTO MAG
10°C 50°F		350	330	310	290	270	250	PTO MAG
20°C 70°F		330	310	290	270	250	230	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 600 HO (Sport R (DPM)/X R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching	Spring	Violet/Violet 414 817 900	←	←	←	←	←	←	←	←	←	←
	Ramp	417 222 596	←	←	←	←	←	←	←	←	←	←
	Calibration screw position	3	4	5	3	4	5					
	Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←					
	Engagement RPM ± 100	3800	←	←	4000	←	←					
	Maximum RPM ± 100	8000	←	←	←	←	←					

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft				
Clutching	Spring	Black 417 126 687	←	←	←	←	←	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	←	←	←	←
	Cam angle	° (degrees)	47° - 44° 417 126 385	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration	Main jet	380	←	←	←	←	←	←	←	←	←	PTO MAG	
	Jet needle	9DHI13-58	←	←	←	←	←	←	←	←	←	2	
	Needle position	N.A.	←	←	←	←	←	←	←	←	←	—	
	Slide cut-away	2.0	←	←	←	←	←	←	←	←	←	2	
	Pilot jet	17.5	←	←	←	←	←	←	←	←	←	2	
	Mixture screw	1.5	←	←	←	←	←	←	←	←	←	—	
	Valve seat	1.5	←	←	←	←	←	←	←	←	←	—	
	Needle jet	N.A.	←	←	←	←	←	←	←	←	←	2	
	Float level	mm	N.A.	←	←	←	←	←	←	←	←	—	
	Idle	RPM ± 200	1600	←	←	←	←	←	←	←	←	—	
	Idle throttle valve position	mm	1.6	1.7	1.8	1.9	2.2	←	←	←	←	—	

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature	- 40°C - 40°F											PTO MAG	
	- 30°C - 20°F											PTO MAG	
	- 20°C - 4°F	380	←	←	←	←	←	←	←	←	←	PTO MAG	
	- 10°C 14°F											PTO MAG	
	0°C 32°F											PTO MAG	
	10°C 50°F											PTO MAG	
	20°C 70°F											PTO MAG	

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 600 (Adrenaline/Adrenaline R/Renegade/Renegade R)

DRIVE PULLEY

Altitude		Sea Level	Altitude				
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Violet/Blue 415 034 900	←	←	←	←	←	
Ramp	417 222 596	←	←	←	←	←	
Calibration screw position	3	4	5	3	4	5	
Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←	
Engagement RPM ± 100	3800	←	←	4000	←	←	
Maximum RPM ± 100	8000	←	←	←	←	←	

DRIVEN PULLEY

Altitude		Sea Level	Altitude				
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Black 417 126 687	←	←	←	←	←	
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	47° - 44° 417 126 385	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) or in deep snow, use 22 tooth sprocket (P/N 504 083 500) to get chaincase ratio of 22/43.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3

CARBURATION

Altitude		Sea Level	Altitude					Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Calibration								
Main jet	380	←	←	←	←	←	PTO MAG	
Jet needle	9DHI13-58	←	←	←	←	←	2	
Needle position	N.A.	←	←	←	←	←	—	
Slide cut-away	2.0	←	←	←	←	←	2	
Pilot jet	17.5	←	←	←	←	←	2	
Mixture screw	1.5	←	←	←	←	←	—	
Valve seat	2.0	←	←	←	←	←	—	
Needle jet	P-0	←	←	←	←	←	2	
Float level	mm	N.A.	←	←	←	←	—	
Idle	RPM ± 200	1600	←	←	←	←	—	
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	

MAIN JET CHART

Altitude		Sea Level	Altitude					Qty
			600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Temperature								
- 40°C - 40°F	410	←	←	←	←	←	PTO MAG	
- 30°C - 20°F	390	←	←	←	←	←	PTO MAG	
- 20°C - 4°F	380	←	←	←	←	←	PTO MAG	
- 10°C 14°F							PTO MAG	
0°C 32°F							PTO MAG	
10°C 50°F							PTO MAG	
20°C 70°F							PTO MAG	

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Summit 600 HO (Adrenaline/Adrenaline R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	←	Green/White 417 222 371	←	←	←	←
	Ramp	←	417 222 552	←	←	←	←
	Calibration screw position	1	1	2	3	4	5
	Pin	417 004 308 (Solid)	417 222 477 (Hollow) no set screw	←	←	←	←
	Engagement RPM ± 100	←	4100	←	←	←	←
	Maximum RPM ± 100	←	8000	←	←	←	←

DRIVEN PULLEY (HPV)

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	←	Red 417 126 686	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	←	N.A.	←	←	←
	Cam angle	° (degrees)	←	50° - 44° 417 126 559	←	←	←

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 308	Pin (Solid)	3

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty	
Calibration	Main jet	←	380	←	←	←	←	PTO MAG	
	Jet needle	←	9DH112-58	←	←	←	←	2	
	Needle position	←	3	←	←	←	←	—	
	Slide cut-away	←	2.0	←	←	←	←	2	
	Pilot jet	←	17.5	←	←	←	←	2	
	Mixture screw	←	1.5	←	←	←	←	—	
	Valve seat	←	1.5	←	←	←	←	—	
	Needle jet	←	P-0	←	←	←	←	2	
	Float level	mm	←	N.A.	←	←	←	←	—
	Idle	RPM ± 200	←	1600	←	←	←	←	—
	Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature	- 40°C - 40°F	←	410	←	←	←	←	PTO MAG
	- 30°C - 20°F	←	390	←	←	←	←	PTO MAG
	- 20°C - 4°F	←	380	←	←	←	←	PTO MAG
	- 10°C 14°F							PTO MAG
	0°C 32°F							PTO MAG
	10°C 50°F							PTO MAG
	20°C 70°F							PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 500 (Adrenaline/Trail)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Green/White 414 222 371	←	←	←	←	←	←
Ramp	417 222 376	←	←	←	←	←	←
Calibration screw position	4	5	6	3	4	5	
Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←	
Engagement RPM ± 100	4400	←	←	4600	←	←	
Maximum RPM ± 100	8000	←	←	←	←	←	

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Beige 414 558 900	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	7.9 17.5	←	←	←	←	←
Cam angle	° (degrees)	42° 417 126 590	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
404 108 600	Pilot jet 20	2
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 107 900	Main jet 420	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
420 239 941	RAVE valve spring (0.8 mm x 52.5 mm). Install above 1800 m (6000 ft)	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		500	470	440	420	390	360	PTO MAG
Jet needle	9HGY1-58	←	←	9HGY4-58	←	←	←	2
Needle position	N.A.	←	←	2	←	←	←	—
Slide cut-away	2.0	←	←	←	←	←	←	2
Pilot jet	17.5	←	←	20	←	←	←	2
Mixture screw	3.0	←	←	2.0	←	←	←	—
Valve seat	1.5	←	←	←	←	←	←	—
Needle jet	N.A.	←	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		520N	500	470	450	420	390	PTO MAG
- 30°C - 20°F		510N	480	450	430	400	370	PTO MAG
- 20°C - 4°F		500	470	440	420	390	360	PTO MAG
- 10°C 14°F		490	460	430	410	380	350	PTO MAG
0°C 32°F		480	450	420	400	370	340	PTO MAG
10°C 50°F		470	440	410	390	360	330	PTO MAG
20°C 70°F		460	430	400	380	350	320	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 500 (Trail R/Adrenaline R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Green/Pink 414 756 900	←	←	Green/Violet 414 762 800	←	←
Ramp		417 222 376	←	←	←	←	←
Calibration screw position		3	4	5	3	4	5
Pin		417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←
Engagement RPM ± 100		4400	←	←	4700	←	←
Maximum RPM ± 100		8000	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet 414 978 300	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←
Cam angle	° (degrees)	44° (anodized) 417 126 445	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
414 762 800	Spring (Green/Violet)	1
404 108 600	Pilot jet 20	2
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 107 900	Main jet 420	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
420 239 941	RAVE valve spring (0.8 mm x 52.5 mm). Install above 1800 m (6000 ft)	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		500	470	440	420	390	360	PTO MAG
Jet needle		9HGY1-58	←	←	9HGY4-58	←	←	2
Needle position		N.A.	←	←	2	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		17.5	←	←	20	←	←	2
Mixture screw		3.0	←	←	2.0	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		N.A.	←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		520N	500	470	450	420	390	PTO MAG
- 30°C - 20°F		510N	480	450	430	400	370	PTO MAG
- 20°C - 4°F		500	470	440	420	390	360	PTO MAG
- 10°C 14°F		490	460	430	410	380	350	PTO MAG
0°C 32°F		480	450	420	400	370	340	PTO MAG
10°C 50°F		470	440	410	390	360	330	PTO MAG
20°C 70°F		460	430	400	380	350	320	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 550 F (Fan R)/Legend 550 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
Clutching												
Spring		Violet/Yellow 415 015 300	←	←	←	←	←	←	←	←	←	←
Block (Bombardier Lite)		417 118 100	←	←	←	←	←	←	←	←	←	←
Weight (Bombardier Lite)		1 x 417 120 400 3 x 417 114 400	← 1 x ← 2 x	← 1 x ← 1 x	1 x 417 120 400	5 x 417 114 400	3 x 417 114 400					
Capsule (Bombardier Lite)		1 x 417 114 500	←	←	←	←	←	←	←	←	←	←
Engagement RPM ± 100		3500	←	3600	3700	3800	←	←	←	←	←	←
Maximum RPM ± 100		6950	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2000 m 8000 ft		3000 m 10000 ft	
Clutching												
Spring		White 504 152 070	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	50° - 47° 417 126 587	←	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
404 119 300	Main jet 165	2
404 112 200	Main jet 180	2
404 119 100	Main jet 210	2
404 118 900	Main jet 230	2
404 100 200	Main jet 240	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
Calibration													
Main jet		250	240	230	210	180	165	PTO MAG					
Jet needle		SG	←	←	←	←	←	←	←	←	←	←	2
Needle position		4	←	←	3	←	←	←	←	←	←	←	—
Slide cut-away		2.5	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		2.0	←	←	←	←	1.5	1.0	←	←	←	←	—
Valve seat		1.2	←	←	←	←	←	←	←	←	←	←	—
Needle jet		P-8 (159)	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.6	1.7	1.8	1.9	2.1	2.4	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
Temperature													
- 40°C - 40°F		260	250	240	220	190	175	165	155	145	135	125	2
- 30°C - 20°F		255	245	235	215	185	170	160	150	140	130	120	2
- 20°C - 4°F		250	240	230	210	180	165	155	145	135	125	115	2
- 10°C 14°F		245	235	225	205	175	160	150	140	130	120	110	2
0°C 32°F		240	230	220	200	170	155	145	135	125	115	105	2
10°C 50°F		235	225	215	195	165	150	140	130	120	110	100	2
20°C 70°F		230	220	210	190	160	145	135	125	115	105	95	2

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Summit 550 F (Fan R)/Grand Touring 550 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Violet/Green 415 015 400	←	←	←	←	←
Block (Bombardier Lite)		417 118 100	←	←	←	←	←
Weight (Bombardier Lite)		1 x 417 120 400 4x 417 114 400	1 x 3 x	1 x 2 x	1 x 1 x	0 x 5 x	0 x 3 x
Capsule (Bombardier Lite)		1 x 417 114 500	←	←	←	←	←
Engagement RPM ± 100		3300	←	3500	3600	3700	3800
Maximum RPM ± 100		6950	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		White 504 152 070	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←
Cam angle	° (degrees)	50° - 47° 417 126 587	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PART TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 119 300	Main jet 165	2
404 112 200	Main jet 180	2
404 119 100	Main jet 210	2
404 118 900	Main jet 230	2
404 100 200	Main jet 240	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		250	240	230	210	180	165	PTO MAG
Jet needle		SG	←	←	←	←	←	2
Needle position		4	←	←	3	←	←	—
Slide cut-away		2.5	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	2
Mixture screw		2.0	←	←	←	1.5	1.0	—
Valve seat		1.2	←	←	←	←	←	—
Needle jet		P-8 (159)	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	—
Idle throttle valve position	mm	1.6	1.7	1.8	1.9	2.1	2.4	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		260	250	240	220	190	175	PTO MAG
- 30°C - 20°F		255	245	235	215	185	170	PTO MAG
- 20°C - 4°F		250	240	230	210	180	165	PTO MAG
- 10°C 14°F		245	235	225	205	175	160	PTO MAG
0°C 32°F		240	230	220	200	170	155	PTO MAG
10°C 50°F		235	225	215	195	165	150	PTO MAG
20°C 70°F		230	220	210	190	160	145	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

MX Z 380 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Blue/Green on Violet 417 126 621	←	←	Violet/Green 415 015 400	←	←					
Block (Bombardier Lite)		417 118 100	←	←	←	←	←	←	←	←	←	←
Weight (Bombardier Lite)		1 x 417 120 400 4 x 417 114 400	← 1 x ← 3 x	← 1 x ← 2 x	1 x 417 120 400	←	←	←	←	←	←	←
Capsule (Bombardier Lite)		1 x 417 114 500	←	←	←	←	←	←	←	←	←	←
Engagement RPM ± 100		3600	3700	3800	3900	←	←	←	←	←	←	←
Maximum RPM ± 100		6800	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Yellow 415 092 800	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	44° 417 126 333	←	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
415 015 400	Spring (Violet/Green)	1
404 123 900	Main jet 120	1
404 130 400	Main jet 135	1
404 130 500	Main jet 145	1
404 118 200	Main jet 160	1
404 123 800	Main jet 170	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		185	170	160	145	135	120	2					
Jet needle		6CDY1	←	←	←	←	←	←	←	←	←	←	2
Needle position		3	3	2	2	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	←	←	←	←	←	—
Valve seat		1.2	←	←	←	←	←	←	←	←	←	←	—
Needle jet		Q-2 (159)	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	←	2.0	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		195	180	170	155	145	130	120	115	110	105	100	2
- 30°C - 20°F		190	175	165	150	140	125	120	115	110	105	100	2
- 20°C - 4°F		185	170	160	145	135	120	115	110	105	100	95	2
- 10°C 14°F		180	165	155	140	130	120	115	110	105	100	95	2
0°C 32°F		175	160	150	135	125	110	105	100	95	90	85	2
10°C 50°F		170	155	145	130	120	110	105	100	95	90	85	2
20°C 70°F		170	155	145	130	120	110	105	100	95	90	85	2

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Legend 380 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Blue/Green on Violet 417 126 621	←	←	Violet/Green 415 015 400	←	←					
Block (Bombardier Lite)		417 118 100	←	←	←	←	←	←	←	←	←	←
Weight (Bombardier Lite)		1 x 417 120 400 4 x 417 114 400	← 1 x ← 3 x	← 1 x ← 2 x	1 x 417 120 400	←	←	←	←	←	←	←
Capsule (Bombardier Lite)		1 x 417 114 500	←	←	←	←	←	←	←	←	←	←
Engagement RPM ± 100		3600	3700	3800	3900	←	←	←	←	←	←	←
Maximum RPM ± 100		6800	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Yellow 415 092 800	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	44° 417 126 333	←	←	←	←	←	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
415 015 400	Spring (Violet/Green)	1
404 123 900	Main jet 120	1
404 130 400	Main jet 135	1
404 130 500	Main jet 145	1
404 118 200	Main jet 160	1
404 123 800	Main jet 170	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		185	170	160	145	135	120	2					
Jet needle		6CDY1	←	←	←	←	←	←	←	←	←	←	2
Needle position		3	3	2	2	←	←	←	←	←	←	←	—
Slide cut-away		2.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	←	←	←	←	←	—
Valve seat		1.2	←	←	←	←	←	←	←	←	←	←	—
Needle jet		Q-2 (159)	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	←	2.0	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		195	180	170	155	145	130	2					
- 30°C - 20°F		190	175	165	150	140	125	2					
- 20°C - 4°F		185	170	160	145	135	120	2					
- 10°C 14°F		180	165	155	140	130	115	2					
0°C 32°F		175	160	150	135	125	110	2					
10°C 50°F		170	155	145	130	120	110	2					
20°C 70°F		170	155	145	130	120	110	2					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Grand Touring 380 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Blue/Green on Violet 417 126 621	←	←	Violet/Green 415 015 400	←	←	
Block (Bombardier Lite)	417 118 100	←	←	←	←	←	
Weight (Bombardier Lite)	1 x 417 120 400 4 x 417 114 400	← 1 x ← 3 x	← 1 x ← 2 x	1 x 417 120 400	←	←	
Capsule (Bombardier Lite)	1 x 417 114 500	←	←	←	←	←	
Engagement RPM ± 100	3600	3700	3800	3900	←	←	
Maximum RPM ± 100	6800	←	←	←	←	←	

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Yellow 415 092 800	←	←	←	←	←	
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←
Cam angle	° (degrees)	44° 417 126 333	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
415 015 400	Spring (Violet/Green)	1
404 123 900	Main jet 120	1
404 130 400	Main jet 135	1
404 130 500	Main jet 145	1
404 118 200	Main jet 160	1
404 123 800	Main jet 170	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		185	170	160	145	135	120	2
Jet needle		6CDY1	←	←	←	←	←	2
Needle position		3	3	2	2	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	2
Mixture screw		1.5	←	←	←	←	←	—
Valve seat		1.2	←	←	←	←	←	—
Needle jet		Q-2 (159)	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	—
Idle throttle valve position	mm	1.7	1.8	1.9	←	2.0	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		195	180	170	155	145	130	2
- 30°C - 20°F		190	175	165	150	140	125	2
- 20°C - 4°F		185	170	160	145	135	120	2
- 10°C 14°F		180	165	155	140	130	115	2
0°C 32°F		175	160	150	135	125	110	2
10°C 50°F		170	155	145	130	120	110	2
20°C 70°F		170	155	145	130	120	110	2

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Grand Touring 500 (Sport/Sport Europe)/Legend 500 (Sport)

DRIVE PULLEY

Clutching	Altitude							
	Sea Level		600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Spring	Violet/Pink 414 949 500		←	←	Violet/Violet 414 817 900	←	←	
Ramp	417 222 376		←	←	417 005 296	←	←	
Calibration screw position	4		5	6	3	4	5	
Pin	417 004 308 (Solid)		←	←	417 004 309 (Hollow)	←	←	
Engagement RPM ± 100	3500		←	←	4000	←	←	
Maximum RPM ± 100	8000		←	←	←	←	←	

DRIVEN PULLEY (HPV)

Clutching	Altitude							
	Sea Level		600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft	
Spring	Violet 414 978 300		←	←	←	←	←	
Spring tension	Kg ± 0.7 lb ± 1.5	N.A.	←	←	←	←	←	
Cam angle	° (degrees)	44° (anodized) 417 126 445	←	←	←	←	←	

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 817 900	Spring (Violet/Violet)	1
417 004 309	Pin (Hollow)	3
417 005 296	Ramp (296)	3
404 108 600	Pilot jet 20	2
404 106 100	Main jet 360	2
404 106 400	Main jet 390	2
404 107 900	Main jet 420	2
404 108 100	Main jet 440	2
404 106 700	Main jet 470	2
420 239 941	RAVE valve spring (0.8 mm x 52.5 mm). Install above 1800 m (6000 ft)	2
404 161 992	Jet needle (9HGY4-58)	2

CARBURATION

Calibration	Altitude							
	Sea Level		600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Main jet	500		470	440	420	390	360	PTO MAG
Jet needle	9HGY1-58		←	←	9HGY4-58	←	←	2
Needle position	N.A.		←	←	2	←	←	—
Slide cut-away	2.0		←	←	←	←	←	2
Pilot jet	17.5		←	←	20	←	←	2
Mixture screw	3.0		←	←	2.0	←	←	—
Valve seat	1.5		←	←	←	←	←	—
Needle jet	N.A.		←	←	←	←	←	2
Float level	mm	N.A.	←	←	←	←	←	—
Idle	RPM ± 200	1600	←	←	←	←	←	—
Idle throttle valve position	mm	1.8	1.9	←	2.0	2.2	←	—

MAIN JET CHART

Temperature	Altitude							
	Sea Level		600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
- 40°C - 40°F	520N		500	470	450	420	390	PTO MAG
- 30°C - 20°F	510N		480	450	430	400	370	PTO MAG
- 20°C - 4°F	500		470	440	420	390	360	PTO MAG
- 10°C 14°F	490		460	430	410	380	350	PTO MAG
0°C 32°F	480		450	420	400	370	340	PTO MAG
10°C 50°F	470		440	410	390	360	330	PTO MAG
20°C 70°F	460		430	400	380	350	320	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Skandic 600 (WT LC/SUV LC)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching	Spring	Red/Red 414 689 800	←	←	Yellow/Red 414 993 000	←	←					
	Ramp	417 005 290	←	←	417 005 291	←	←					
	Calibration screw position	3	4	5	2	3	4					
	Pin	417 004 308 (Solid)	←	←	417 004 309 (Hollow)	←	←					
	Engagement RPM ± 100	3600	←	←	←	←	←					
	Maximum RPM ± 100	7000	←	←	←	←	←					

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching	Spring	Blue ACS 3-188 (417 119 100)	←	←	←	←	←	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	7.0 15.4	←	←	←	←	←	←	←	←	←
	Cam angle	° (degrees)	40°	←	←	←	←	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
417 004 309	Pin (Hollow)	3
417 005 291	Ramp	3
414 993 000	Spring (Yellow/Red)	1
404 161 979	Main jet 215	2
404 100 200	Main jet 240	2
404 100 600	Main jet 260	2
404 101 100	Main jet 290	2
404 107 800	Main jet 310	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration	Main jet	330	310	290	260	240	215	PTO MAG					
	Jet needle	6FL14	←	←	←	←	←	←	←	←	←	←	2
	Needle position	5	←	←	4	←	←	←	←	←	←	←	—
	Slide cut-away	2.5	←	←	←	←	←	←	←	←	←	←	2
	Pilot jet	40	←	←	←	←	←	←	←	←	←	←	2
	Mixture screw	1.5	←	←	←	1.0	←	←	←	←	←	←	—
	Valve seat	1.5	←	←	←	←	←	←	←	←	←	←	—
	Needle jet	P-9 (480)	←	←	←	←	←	←	←	←	←	←	2
	Float level	mm	18.1	←	←	←	←	←	←	←	←	←	—
	Idle	RPM ± 200	1500	←	←	←	←	←	←	←	←	←	—
	Idle throttle valve position	mm	1.5	←	1.6	1.8	1.9	2.0	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature	- 40°C - 40°F	350	330	300	280	250	230	PTO MAG					
	- 30°C - 20°F	340	320	290	270	250	220	PTO MAG					
	- 20°C - 4°F	330	310	290	260	240	215	PTO MAG					
	- 10°C 14°F	320	300	280	250	230	210	PTO MAG					
	0°C 32°F	310	290	270	240	220	200	PTO MAG					
	10°C 50°F	300	280	260	230	210	190	PTO MAG					
	20°C 70°F	290	270	250	220	205	185	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Skandic 500 F (Fan SWT R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Yellow/Orange 414 689 700	←	←	←	←	Blue/Yellow 414 689 500
	Ramp	417 005 290	←	←	←	←	←
	Calibration screw position	2	3	4	5	6	3
	Pin	417 004 309 (Hollow)	←	←	←	←	←
	Engagement RPM ± 100	3000	←	←	←	←	3300
	Maximum RPM ± 100	6800	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching	Spring	Blue ACS 3-188 (417 119 100)	←	←	←	←	←
	Spring tension	Kg ± 0.7 lb ± 1.5	7.0 15.4	←	←	←	←
	Cam angle	° (degrees)	40°	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 689 500	Spring (Blue/Yellow)	1
404 130 400	Main jet 135	2
404 130 500	Main jet 145	2
404 128 700	Main jet 155	2
404 119 300	Main jet 165	2
404 119 200	Main jet 175	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty	
Calibration	Main jet	185	175	165	155	145	135	PTO MAG	
	Jet needle	6DH2	←	←	←	←	←	2	
	Needle position	3	←	←	2	←	←	—	
	Slide cut-away	2.5	←	←	←	←	←	2	
	Pilot jet	40	←	←	←	←	←	2	
	Mixture screw	2.0	←	←	2.5	←	←	—	
	Valve seat	1.5	←	←	←	←	←	—	
	Needle jet	P-1 (159)	←	←	←	←	←	2	
	Float level	mm	23.9	←	←	←	←	←	—
	Idle	RPM ± 200	1650	←	←	←	←	←	—
	Idle throttle valve position	mm	1.5	←	1.6	1.7	1.8	1.9	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature	- 40°C - 40°F	195	185	175	165	155	145	PTO MAG
	- 30°C - 20°F	190	180	170	160	150	140	PTO MAG
	- 20°C - 4°F	185	175	165	155	145	135	PTO MAG
	- 10°C 14°F	180	170	160	150	140	130	PTO MAG
	0°C 32°F	175	165	155	145	135	125	PTO MAG
	10°C 50°F	170	160	150	140	130	120	PTO MAG
	20°C 70°F	165	155	145	135	125	115	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Skandic 500 F (Fan WT R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Yellow/Orange 414 689 700	←	←	←	←	←	←	←	←	←	←
Ramp		417 005 290	←	←	←	←	←	←	←	←	←	←
Calibration screw position		4	5	6	2	3	4					
Pin		417 004 309 (Hollow)	←	←	←	←	←	←	←	←	←	←
Engagement RPM ± 100		3000	←	←	3300	←	←	←	←	←	←	←
Maximum RPM ± 100		6800	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Blue ACS 3-188 (417 119 100)	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	7.0 15.4	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	40°	←	←	←	←	←	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 817 700	Spring (Blue/Green)	1
404 130 400	Main jet 135	2
404 130 500	Main jet 145	2
404 128 700	Main jet 155	2
404 119 300	Main jet 165	2
404 119 200	Main jet 175	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		185	175	165	155	145	135	PTO MAG					
Jet needle		6DH2	←	←	←	←	←	←	←	←	←	←	2
Needle position		3	←	←	2	←	←	←	←	←	←	←	—
Slide cut-away		2.5	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		40	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		2.0	←	←	2.5	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		P-1	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.5	←	1.6	1.7	1.8	1.9	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Temperature													
- 40°C - 40°F		195	185	175	165	155	145	PTO MAG					
- 30°C - 20°F		190	180	170	160	150	140	PTO MAG					
- 20°C - 4°F		185	175	165	155	145	135	PTO MAG					
- 10°C 14°F		180	170	160	150	140	130	PTO MAG					
0°C 32°F		175	165	155	145	135	125	PTO MAG					
10°C 50°F		170	160	150	140	130	120	PTO MAG					
20°C 70°F		165	155	145	135	125	115	PTO MAG					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Skandic 500 F (Fan SPORT R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	Red/Yellow 414 817 500	←	←	Blue/Violet 414 817 800	←	←	
Ramp	417 005 296	←	←	←	←	←	
Calibration screw position	3	4	5	3	4	5	
Pin	417 004 309 (Hollow)	←	←	←	←	←	
Engagement RPM ± 100	3500	←	←	4000	←	←	
Maximum RPM ± 100	6700	←	←	6800	←	←	

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2000 m 8000 ft	3000 m 10000 ft
Clutching							
Spring	White 504 152 070	←	←	←	←	←	
Spring tension	Kg ± 0.7 lb ± 1.5	0.0	←	←	←	←	←
Cam angle	° (degrees)	48° - 44° 417 126 685	←	←	←	←	←

Additional information: At and above 2400 m (8000 ft) connect reverse connector (P/N 515 174 700) to E-box.

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
414 817 800	Spring (Blue/Violet)	1
404 153 100	Pilot jet 45	2
404 130 400	Main jet 135	2
404 120 900	Main jet 150	2
404 119 300	Main jet 165	2
404 112 200	Main jet 180	2
404 119 400	Main jet 195	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		210	195	180	165	150	135	PTO MAG
Jet needle		6AFY-5	←	←	←	←	←	2
Needle position		4	4	3	3	←	←	—
Slide cut-away		2.0	←	←	←	←	←	2
Pilot jet		40	←	←	45	←	←	2
Mixture screw		1.5	←	←	2.0	←	←	—
Valve seat		1.2	←	←	←	←	←	—
Needle jet		P-4 (159)	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	—
Idle throttle valve position	mm	1.9	2.0	2.1	2.2	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		220	210	190	175	160	145	PTO MAG
- 30°C - 20°F		220	200	185	170	155	140	PTO MAG
- 20°C - 4°F		210	195	180	165	150	135	PTO MAG
- 10°C 14°F		205	190	175	160	145	130	PTO MAG
0°C 32°F		200	185	170	155	140	125	PTO MAG
10°C 50°F		195	180	165	150	135	120	PTO MAG
20°C 70°F		195	180	165	150	135	120	PTO MAG

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Skandic 440 F (Fan LT R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Silver M140032	←	←	←	←	←	←	←	←	←	←
Ramp		M140030	←	←	←	←	←	←	←	←	←	←
Calibration screw position		N.A.	—	—	—	—	—	—	—	—	—	—
Pin		N.A.	—	—	—	—	—	—	—	—	—	—
Engagement RPM ± 100		3200	←	←	←	←	←	←	←	←	←	←
Maximum RPM ± 100		6900	←	←	←	←	←	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft	
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft				
Clutching												
Spring		Yellow 415 092 800	←	←	←	←	←	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3	←	←	←	←	←	←	←	←	←	←
Cam angle	° (degrees)	40°	←	←	←	←	←	←	←	←	←	←

Additional Information: At and above 2400 m (8000 ft) use reverse connector (P/N 515 174 700).

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
M207758A	Spring (Purple)	1
404 123 900	Main jet 120	2
404 124 900	Main jet 130	2
404 130 500	Main jet 145	2
404 128 700	Main jet 155	2
404 123 800	Main jet 170	2

CARBURATION

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
Calibration													
Main jet		180	170	155	145	130	120	PTO MAG					
Jet needle		6DGY12	←	←	←	←	←	←	←	←	←	←	2
Needle position		3	←	2	←	←	←	←	←	←	←	←	—
Slide cut-away		3.0	←	←	←	←	←	←	←	←	←	←	2
Pilot jet		50	←	←	←	←	←	←	←	←	←	←	2
Mixture screw		1.5	1.75	←	2.0	←	←	←	←	←	←	←	—
Valve seat		1.5	←	←	←	←	←	←	←	←	←	←	—
Needle jet		(159) 0-0	←	←	←	←	←	←	←	←	←	←	2
Float level	mm	23.9	←	←	←	←	←	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	←	←	←	←	←	—
Idle throttle valve position	mm	1.4	1.6	1.8	←	2.0	←	←	←	←	←	←	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft		1200 m 4000 ft		1800 m 6000 ft		2400 m 8000 ft		3000 m 10000 ft		Qty
			Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
- 40°C - 40°F		190	180	165	155	140	130	1					
- 30°C - 20°F		185	175	160	150	135	125	1					
- 20°C - 4°F		180	170	155	145	130	120	1					
- 10°C 14°F		175	165	150	140	125	115	1					
0°C 32°F		170	160	145	135	120	110	1					
10°C 50°F		165	155	140	130	120	110	1					
20°C 70°F		165	155	140	130	120	110	1					

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.

Tundra 280 F (Fan R)/Skandic 280 F (Fan R)

DRIVE PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Red/Yellow 414 817 500	←	←	←	←	←
Block (Bombardier Lite)		417 114 300	←	←	←	←	←
Weight (Bombardier Lite)		5 x 417 114 400	4 x ←	3 x ←	2 x ←	1 x ←	←
Capsule (Bombardier Lite)		1 x 417 114 500	←	←	←	←	←
Engagement RPM ± 100		3000	3100	3200	3300	←	←
Maximum RPM ± 100		6900	←	←	←	←	←

DRIVEN PULLEY

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Clutching							
Spring		Yellow 415 094 300	←	←	←	←	←
Spring tension	Kg ± 0.7 lb ± 1.5	0.0 Position 3 0.0	←	←	←	←	←
Cam angle	° (degrees)	37.8° 417 126 350	←	←	←	←	←

CAUTION: The following adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow conditions. Always observe spark plug condition for proper jetting.

PARTS TO BE INSTALLED

P/N	DESCRIPTION	QTY
404 126 600	Main jet 140	1
404 120 900	Main jet 150	1
404 118 200	Main jet 160	1
404 119 500	Main jet 185	1
404 119 400	Main jet 195	1

CARBURATION

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Calibration								
Main jet		200	195	185	160	150	140	1
Jet needle		6DH4	←	←	←	←	←	1
Needle position		3	←	←	2	←	←	—
Slide cut-away		2.5	←	←	←	←	←	1
Pilot jet		40	←	←	←	←	←	1
Mixture screw		1.0	←	←	0.75	←	←	—
Valve seat		1.5	←	←	←	←	←	—
Needle jet		0-8 (159)	←	←	←	←	←	1
Float level	mm	23.9	←	←	←	←	←	—
Idle	RPM ± 200	1650	←	←	←	←	←	—
Idle throttle valve position	mm	1.5	1.6	1.7	1.8	1.9	2.0	—

MAIN JET CHART

Altitude		Sea Level	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	Qty
Temperature								
- 40°C - 40°F		220	210	200	180	170	160	1
- 30°C - 20°F		210	200	190	170	160	150	1
- 20°C - 4°F		200	195	185	160	150	140	1
- 10°C 14°F		195	190	180	155	145	135	1
0°C 32°F		190	185	175	150	140	130	1
10°C 50°F		180	175	165	140	130	120	1
20°C 70°F		175	170	160	135	125	115	1

NOTE: Arrows in the charts indicate that the preceding information is repeated.

NOTE: Shaded column gives factory settings.